

1     **PNEUMATIC TOOL ACCESSORY PROVIDED WITH MEANS TO**

2     **MONITOR INTENSITY OF STRESS EXERTING THEREON**

3     **BACKGROUND OF THE INVENTION**

4     **1. FILED OF THE INVENTION**

5             The present invention relates generally to a pneumatic tool, and more  
6 particularly to a pneumatic tool accessory which is provided with a stress  
7 monitoring structure for checking intensity of stress exerting thereon, so as to  
8 avert breakage or damage of the pneumatic tool accessory or workpiece.

9     **2. BACKGROUND OF THE INVENTION**

10            The conventional pneumatic tool accessory is not provided with a  
11 stress monitoring structure by which the straining force exerting on the  
12 pneumatic tool accessory or workpiece is so checked as to prevent damage to  
13 the accessory itself or workpiece. The conventional pneumatic tool accessory,

14 such as adaptor, connection rod, or the like, has a predetermined stress limit.

15 However, the stress limit of a number of accessories of the same kind is apt to  
16 change in the event that they are made in batch, or that they are made by  
17 different materials or under different processing conditions. As a result, a user  
18 of the conventional pneumatic tool accessories is often in the dark as to the  
19 torsional limits of the accessories. Under such circumstances as described  
20 above, the conventional pneumatic tool accessories are prone to damage or  
21 breakage when they are put to work.

## SUMMARY OF THE INVENTION

The primary objective of the present invention is to provide a pneumatic tool accessory with a stress monitoring structure enabling a user of the pneumatic tool accessory to be aware of a fact that the strain exerting on the pneumatic tool accessory is about to reach a dangerous threshold.

In keeping with the principle of the present invention, the foregoing objective of the present invention is attained by the pneumatic tool accessory which is provided on a body thereof with a stress monitoring structure comprising a stress intensity control and a stress intensity monitor. The stress intensity control serves as a breaking point of the body of the pneumatic tool accessory while the stress intensity monitor is formed of a reference line and an indicator line which is aligned with the reference line. When the body of the pneumatic tool accessory is exerted on by an excessive straining force, the body tends to deform to result in nonalignment of the indicator line with the reference line.

The features and the advantages of the present invention will be more readily understood upon a thoughtful deliberation of the following detailed description of the preferred embodiments of the present invention with reference to the accompanying drawings.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 shows a perspective view of a first preferred embodiment of the present invention;

Fig. 2 shows a schematic plan view of the first preferred embodiment of the present invention;

Fig. 3 shows a schematic plan view of a deformation of the first preferred embodiment of the present invention;

Fig. 4 shows a perspective view of a second preferred embodiment of the present invention;

Fig. 5 shows a schematic plan view of the second preferred embodiment of the present invention; and

Fig. 6 shows a schematic plan view of a deformation of the second preferred embodiment of the present invention.

---

## **DETAILED DESCRIPTION OF THE INVENTION**

As shown in FIG. 1 and FIG. 2, a pneumatic tool accessory 10 of the present invention has a body 11 of a length. The body 11 is provided with a stress monitoring structure comprising a stress intensity control portion 20 and a stress intensity monitor 30. The stress intensity control portion 20 is a recessed portion smaller in outer diameter than the body 11. The recessed portion 20 is located at a midpoint of the body 11. The stress intensity monitor 30 is formed of an indicator line 31, and a reference line 32 which is separated

1 from the indicator line 31 by the recessed portion 20. The indicator line 31 is  
2 aligned with the reference line 32, as shown in FIG. 2.

3 As illustrated in FIG. 3, the recessed portion 20 is caused to deform  
4 by a straining force exerting thereon, thereby resulting in nonalignment of the  
5 indicator line 31 with the reference line 32. Such nonalignment is indicative of  
6 an excessive stress produced in the body 11. If the excessive stress is allowed  
7 to persist, the stress intensity control portion 20 (the recessed portion) is bound  
8 to break. In another words, the stress intensity control portion 20 serves as a  
9 breaking point. As a result, the present invention is capable of preventing a  
10 damage to the pneumatic tool or workpiece. In addition, the present invention  
11 serves to minimize the occupational hazard, so as to enhance the safety of a  
12 worker using the pneumatic tool accessory.

13 As shown in FIGS. 4 and 5, the body 11 of the present invention is  
~~14 provided with a stress monitoring structure comprising a stress intensity~~  
15 control portion (the recessed portion) 20, and a stress intensity monitor 30A  
16 which is formed of an indicator point 31A and a reference point 32A. The  
17 indicator point 31A is aligned with the reference point 32A, as shown in FIG.  
18 5.

19 As illustrated in FIG. 6, the recessed portion 20 is caused to deform  
20 by a straining force exerting thereon, thereby resulting in nonalignment of the  
21 indicator point 31A with the reference point 32A. The nonalignment is  
22 indicative of an excessive stress produced in the body 11. In the event that the

body 11 is not relieved of the excessive stress, a breakage is bound to take place in the stress intensity control portion 20.

The stress intensity monitor 30A is further formed of two warning points 33A which are opposite in location to each other and are located equidistantly from the reference point 32A such that the two warning points 33A and the reference point 32A are arranged in a straight line.

As soon as one of the two warning points 33A is aligned with the indicator point 31A, the body 11 should be immediately relieved of the strain exerting thereon, so as to avert breakage of the body 11.

The embodiments of the present invention described above are to be regarded in all respects as being illustrative and nonrestrictive. Accordingly, the present invention may be embodied in other specific forms without deviating from the spirit thereof. The present invention is therefore to be

~~limited only by the scopes of the following claims.~~